


CARBON CLEAN RANGE COMPARISON

	CC-14	CC-16	CC-18
			
 APPLICATION	 UP TO 2L		
 INPUT POWER	220 V AC 1PH	220 V AC 16A 1PH	220 V AC (32-50A) 1PH/3PH
 POWER GENERATION	1.4 KW/H	4 KW/H	6.6 KW/H
 WEIGHT	40 KG	115 KG	175 KG
 DISPLACEMENT	Constant Gas Flow	Variable Gas Flow	Variable Gas Flow
 ENGINE RANGE SELECTION	N/A (600L Constant)	1.0 - 1.9 2.0 - 2.9 3.0 - 3.9 4.0 +	4.0 - 8.0 8.0 - 12.0 12.0 - 16.0 16.0 +
 TANK SIZE	8L	24L	48L
 ELECTROLYTE SUPPLIED WITH UNIT	2 KGS	4 KGS	8 KGS
 RATIO OF ELECTROLYTE TO WATER TO BE USED*	1:10 - 2:10 Electrolyte Soln	1:10 - 2:10 Electrolyte Soln	1:10 - 2:10 Electrolyte Soln
 CELLS	3 x 3 RAID Technology (Generators)	9 x 9 RAID Technology (Generators)	18 x 18 RAID Technology (Generators)
 CELL TYPE	Wet cell	Wet cell	Wet cell

*Not essential but recommended.

Carbon Clean Ltd.
181 Forest Rd
Hainault
Essex, IG6 3HZ, UK



+44 (0)203 507 0175
Info@carbon-clean.co.uk
www.carbon-clean.co.uk

